

EBB90





Refrigeration System

- · Side mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.
- · Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- · Full-length air duct ensures optimal cold air circulation.
- · Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- · Large capacity, corrosion-resistant condenser and evaporator coils.
- · Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
- · High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.

- · Galvanized steel interior walls and high quality stainless steel floor.
- · 13/4" thick high density polyurethane insulation.
- · Built-in caster thread receptacles.

Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

Doors

- · Textured laminate, black vinyl exterior with galvanized steel interior.
- ·13/4" thick high density polyurethane insulation.
- · Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, recessed door handles.
- · Pre-installed door locks keep your items safe from theft.

Shelving

- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.

Temperature Control

- · Multi-function digital controller with easy to read LED display.
- · Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- · Audible overheat protection alarm for compressor and condenser coil.

Options

- · Additional shelving.
- · 3" or 5" swivel casters with locks.
- · 3.5" 6" height-adjustable and interchangeable legs.



















Туре	Doors	Capacity Cu. Ft.	12 oz. Cans	12 oz. Bottles	Shelves	Refrigerant	НР	Power V-Hz-Ph	Amps	Crated Weight	Exterior Dimensions		
											L	D	H*
REF	3	32	1120	696	6	R-290	1/3	115-60-1	2.5	450 lbs	89.25"	27"	37.25"

BACK BAR COOLER



EBB90

EBB Series

DIMENSIONAL DATA

	L	89.25 in.	
External Dims.	D	27 in.	
	H*	37.25 in.	
Crated Weight	450 lbs.		
_			
Doors/Drawers/	Lids	3	

STORAGE DATA

Net Capacity Cu. Ft. 🟲	32
Shelves	6
Barrels	-
20 oz. Bottles	-
12 oz. Bottles	696
12 oz. Cans	1120
8" Mugs	-
# of Pans (Top)	-
# of Pans (Drawer)	-
Dividers	-
Trays	-

ELECTRICAL DATA

Voltage	115-60-1
Full Load Amperage	2.5A
Feed Wires w/ Ground	3
Cord Length	9ft
NEMA Plug Type	(i) NEMA 5-15P


REFRIGERATION DATA


	• • •
Compressor	Side
Refrigerant	R-290
Compressor HP	1/3
BTU/HR [†]	2311

KEY


D Door		R	Refriger)		
L Lid		REF	Refriger			
H Half Door		F	Freezer			
FD Full Door		FRZ	Freezer			
SD Solid Door		DUAL	REF/FRZ			
GD Glass Door		DR	Drawer			
		Elevation	Right	Plan	3D	Back


PLAN VIEW





FRONT





SIDE

TOP

AIRFLOW

ACCESSORIES & OPTIONS

- Additional Shelving
- AJL03-01
- CASA3-02
- CASA5-02
- Contact Everest Refrigeration for more information.
- Interchangeable Leg for Caster (Optional)
- 3" Overall Height Caster Assembly (3) Front (3) Rear
- 5" Overall Height Caster Assembly (3) Front (3) Rear